


LED floor lamp MAULsenja colour vario sensor, dimmable







- · High-quality, powerful aluminium design lamp with modern light management
- · Constant light control via movement and daylight sensors
- · Colour temperature and intensity infinitely adjustable
- · Large lamp head: For double workstations and illuminating the entire desk surface
- Separately controllable: Beam direction 80 % upwards (indirect room lighting) and 20 % downwards (direct light for work surface)
- · Very economical: State of the art LED technology
- · GS label for checked safety, technical safety concept Made by MAUL
- · Designed by MAUL: Developed and constructed in Germany
- Movement sensor: Dims the light automatically after 30 minutes without sensing movement, turns off after a further 30 minutes without sensing movement
- Daylight sensor: The light output of the lamp changes depending on the indoor illuminance level
- · Head and column made from high-quality aluminium
- Long lamp head: Protrudes 80 cm over the desk
- Light source and operating device replaceable by an electrician
- · Recyclable packaging
- Available from 08 / 2024

Illuminance of the: 940 lux illuminance at 85 cm distance, 580 lux illuminance at 110 cm distance

Colour temperature per light source: 2.700 Kelvin (warm white) to 5.700 Kelvin (daylight white)

Number of light sources:

Energy efficiency class per light source: indirect: C (spectrum A to G) & direct: D (spectrum A to G) Weighted energy consumption per light source: 87 kWh/1000 h (69 kWh/1000 h & 18 kWh/1000 h)

Service life L70B50 per light source: 50.000 h

Useful luminous flux per light source: 15.150 Lumen (12.500 Lumen & 2.650 Lumen)

Material: Head: Aluminium, metal - Column: Aluminium, metal

Dimensions: Head: 79.2 x 24 x 3.1 cm

Movement: Head: fixed

• Stabiler, massiver Standfuß aus Stahl, 27 x 45,5 cm. Steht nicht im Weg: Ausgeschnittene Fußplatte kann um ein Tischbein herum positioniert werden. Höhe: 196 cm

· Guarantee: 2 years

Art. No.	Colour	EAN-Code	Tariff-No.	Enthaltene Lichtquellen	Cable length (approx.)	Protection class	Pack size / PU	Weight (incl. packaging)	PU
8258802	white	4002390091411	94052190	-8258809.200, 8258809.205	2.50 m	I shock-proof plug	120 x 50 x 12 cm	15.1 kg	1 pc(s).
8258895	silver	4002390091398	94052190	-8258809.200, 8258809.205	2.50 m	I shock-proof plug	120 x 50 x 12 cm	15.1 kg	1 pc(s).