



Markeringstape DURALINE® 50/05

Artikel nr.	102105	Antal salgsenheder	1 Piece
Farve	Green	Salgsenhed EAN	4005546999821
Emballageenhed	stk	Emballagevægt (brutto)	1380.4 G
Basis EAN	4005546999821	Oprindelsesland	GB



Logoer og udmærkelser



Produkt beskrivelse

- Selvklæbende markeringstape til indendørs brug
- Skridsikring (R-gruppe) R9 i henhold til tysk arbejdsmiljølov, ASR A1.5-1,2 »Gulv«, i henhold til DIN 51130
- Til permanent markering af gangarealer og kørebaner i lagerbygninger og fabrikker
- Egnet til at blive kørt over med gaffeltrucks, undtagen ved styre-, bremse- og drejebævevælgelser
- Tykkelse: 0,5 mm
- 50 mm x 33 m (B x L)
- Farver i overensstemmelse med RAL 9003 signalthvid, 3001 signalrød, 1003 signalgul, 6032 signalgrøn, 5005 signalblå

Produkt detaljer

Udvendig brede (mm)	50
Udvendig dybde / længde	30 m

102105_PDS_DURABLE_da_DK.pdf | 2026-03-16 07:10

1/2

DURABLE Hunke & Jochheim GmbH & Co. KG
Westfalenstraße 77 - 79 · 58636 Iserlohn · Germany
Phone +49 (0) 2371 662 0 · Fax +49 (0) 2371 662 221
Mail durable@durable.de | durable.de

The statements contained herein are for informational purposes only and are true and accurate to the best of our scientific and technical knowledge. This information does not constitute a guarantee or warranty, express or implied, nor does it establish a legally valid contractual relationship. It is the customer's responsibility to determine the suitability of this product for the customer's intended use. DURABLE does not assume any liability for the customer's use of this product or the information contained herein.




Markeringstape DURALINE® 50/05

Brand	DURABLE
Type af selvkøbende	Permanent
Klæbestyrke	Nejrmal
Modstandsdygtighed	Nejrmal
Materiel tykkelse	0.5 mm
Speciel farve	Lignende RAL 6032 signalgrøn
Anvendelsesområde	Gangområde, kørselsområde, egnet til gaffeltrucks
Diameter af rullens holder (mm)	76
Teknisk standard	ASR A1.5/1.2 "Gulv" i henhold til DIN 51130 Skridsikkerhed (R-gruppe) R9

Markeringstape DURALINE® 50/05

Artikel nr.	102105	Antal salgsenheder	1 Piece
Farve	Green	Basis EAN	4005546999821



Oplysninger om materialer

Folie (produkt)	PVC-P (blød)	3
Lim	Akrylatlim	

3 Blødgøreren i denne produktbestanddel af PVC-P (blød PVC) er ikke REACH-oplysningspligtig og ikke en SVHC.
 Dioctylterephthalat [bis(4-ethylhexyl) benzen-, -dicarboxylat (DOTP/DEHT)
 CAS-nr. 6422-86-2
 EINECS-nr. 229-176-9
 [retsgrundlag: REACH-forordningen (EF) nr. 1907/2006, Artikel 57, Bilag XIV]
 Denne blødgører er ikke anført i REACH-kandidatlisten og er tilladt som plastmateriale bestemt til kontakt med fødevarer (i henhold til Forordning (EU) nr. 10/2011, bilag 1, tabel 1, FCM-substans nr. 798 / ref.-nr. 92200 / additiver) og også tilladt i produkter til børn (i henhold til Direktiv 2009/49/EU DIN EN 71-1:2015-02).

102105_MDS_DURABLE_da_DK.pdf | 2026-03-16 03:21

1/1

Oplysninger om REACH- / SVHC-kandidatliste:

Ifølge erklæringerne fra vores leverandører af råvarer, er ingen af stofferne på den aktuelle SVHC-kandidatliste brugt i produktionen af disse råvarer, og sådanne stoffer er heller ikke tilsat bevidst. Hvor dette ikke gælder for et underprodukt, finder du en detaljeret substansbeskrivelse i afsnittet med materialeinformation.
 Allestedsnærværende spor af stoffer på listen over SVHC-kandidater kan ikke udelukkes. Råvarer og produkter fremstillet af os er ikke specifikt analyseret for SVHC-kandidatlistestoffer.


DURABLE Hunke & Jochheim GmbH & Co. KG
 Westfalenstraße 77 – 79 · 58636 Iserlohn · Germany
 Phone +49 (0) 2371 662 0 · Fax +49 (0) 2371 662 221
 Mail durable@durable.de | durable.de

The statements contained herein are for informational purposes only and are true and accurate to the best of our scientific and technical knowledge. This information does not constitute a guarantee or warranty, express or implied, nor does it establish a legally valid contractual relationship. It is the customer's responsibility to determine the suitability of this product for the customer's intended use. DURABLE does not assume any liability for the customer's use of this product or the information contained herein.



Technical Datasheet

FLOOR MARKING TAPE DURALINE® 50/05



Art. No. 102105
Colour green (RAL 6032)
EAN 4005546999821

For safety and orientation in storage and operations: Self-adhesive floor marking tape for the long-term marking of parking spaces, safety zones, walkways and driveways.

Technical information

Foil		
floor tape	PVC-P foil	
colour	signal green (RAL 6032)	
execution	Straight cutted edges	
R-value	R9	according to DIN 51130:2014-02
Dimensions		
foil thickness (mm)	0,5	
adhesive base	modified solvent acrylic	
thickness adhesive layer (mm)	0,13	
liner	Siliconized paper liner	
thickness liner	0,13 mm	
total thickness	0,76 mm	
width (mm)	50	
length (m)	30	
Adhesion properties		
initial tack (kg/cm)	< 6	according PSTC-6
holding power (hr/25°C/cm²)	> 24	according ASTM-7
adhension to steel (kg/25,4 mm²)	> 6	according to PSTC-1
temperature resistance	-30° C to +70° C	1 h/° C
Packing		
packaging	1 pc. / PE bag / corrugated carton	
weight	1.300 g/piece	
Storage		
storage	in original packaging, store in following conditions	
storage conditions (approx.)	+17° to 21° C / 50 to 55 % humidity (RF)	
storage time	18 months	

DURABLE

Hunke & Jochheim GmbH & Co. KG
Westfalenstraße 77-79
D-58636 Iserlohn

Telefon +49 (0) 2371 / 662 – 0
Telefax +49 (0) 2371 / 662 – 221
Internet www.durable.de
E-Mail durable@ durable.de

The statements contained herein are for informational purposes only and are true and accurate to the best of our scientific and technical knowledge. This information does not constitute a guarantee or warranty, express or implied, nor does it establish a legally valid contractual relationship. It is the customer's responsibility to determine the suitability of this product for the customer's intended use. DURABLE does not assume any liability for the customer's use of this product or the information contained herein.



Processing temperatures	
minimum underground application temperature	+10° C
advised application temperature	+15°C to 25° C

Application	
areas of application	indoor use

Resistance	
UV	good
weather	variable
mineral oils	good
vegetable oils	good
collant (containing compounds of esters and amines)	good
alkaline liquids (pH 7 - 9,5)	good
powerful alkaline liquids (pH 9,5 – 14)	variable
acids (pH 2 – 7)	good
powerful acids (pH 0 – 2)	variable
disinfectants	good
alcohol	good
chloride solutions	variable
solvents (aromatic aliphatic)	variable
halogenated solvents	variable
plasticizers like phthalates	slow degradation
acetat and aldehyde	low
ketones (acetone)	low

Application Information	
floor conditions	The surface must be dry, firm, flat and closed and free of dirt, grease, dust, tar, wax and other dirt. In the case of heavy soiling, clean beforehand with a commercially available IPA cleaner (isopropyl alcohol 99,9 %). Never use cleaners that contain chlorine or citrus. Always clean with water and soap after cleaning with degreasing agent. After cleaning, wait at least half an hour until the surface has completely dried. Only then apply DURALINE®. A primer is recommended on concrete, wood and asphalt.
application	Before using DURALINE®, you should first use a test strip to check whether the floor is suitable for DURALINE®. Mark the place where DURALINE® is to be attached. Then remove approx. 10 cm of the protective film and press the material with the adhesive side firmly onto the floor. Unroll as much material as you need. Remove the protective film with one hand while pressing the material with your other hand. For a better adhesive result, we recommend a pressure roller in order to press the material evenly over the entire surface. Please do not glue the material overlapping.
usage	After attaching, the material is immediately accessible on foot, full usage is possible after 48 hours.

cleaning	DURALINE® can be cleaned with (warm) water and commercially available cleaning agents.
removing DURALINE®	Start pulling the material off the floor at one corner. Heat facilitates removal; a temperature of 60° - 70° C is ideal. To remove adhesive residues, we recommend alcohol or a strong solvent. Test the compatibility on the floor beforehand.
warranty	DURALINE® products are conditionally warranted 2 years from purchase. Warranty claims are only limited to replacement of DURALINE. The warranty does not cover the maneuvering of vehicles or items being dragged, pushed or scraped across such as pallets or transit skids.
Note	All technical data represent non-binding average values. Appropriate tests should decide on the usability. We reserve the right to make changes in the course of technical progress to improve the product.

DURABLE

Hunke & Jochheim GmbH & Co. KG
Westfalenstraße 77-79
D-58636 Iserlohn

Telefon +49 (0) 2371 / 662 – 0
Telefax +49 (0) 2371 / 662 – 221
Internet www.durable.de
E-Mail durable@durable.de

The statements contained herein are for informational purposes only and are true and accurate to the best of our scientific and technical knowledge. This information does not constitute a guarantee or warranty, express or implied, nor does it establish a legally valid contractual relationship. It is the customer's responsibility to determine the suitability of this product for the customer's intended use. DURABLE does not assume any liability for the customer's use of this product or the information contained herein.

